



**Product Specification**

**1.27mm PITCH 2X44P 1272WVS CONNECTOR SERIES**

**Table of Content**

<b>1. SCOPE.....</b>	<b>2</b>
<b>2. REFERENCE DOCUMENTS.....</b>	<b>2</b>
<b>3. MATERIAL AND COMPONENT.....</b>	<b>2</b>
<b>4. DESIGN AND CONSTRUCTION.....</b>	<b>2</b>
<b>5. PERFORMANCE AND TEST DESCRIPTIONS.....</b>	<b>3</b>
5.1 Electronic Performance.....	3
Contact Resistance	
Insulation Resistance	
Dielectric Withstanding Voltage	
5.2 Mechanical Performance.....	5
Contact Retention	
Durability	
Solderability	
Vibration	
Physical Shock	
5.3 Environment Performance.....	6
Humidity	
Thermal Shock	
Salt Spray	
Temperature Life	
Resistance to Soldering Heat	



## Product Specification

### 1.27mm PITCH 2X44P 1272WVS CONNECTOR SERIES

## 1. Scope:

This specification covers the requirements for product performance, test methods and quality assurance provisions of **1.27mm PITCH 2X44PIN CONNECTOR**

## 2. Reference Documents :

The following documents form a part of this specification to the extent specified herein. In the event of conflict between the requirements of this specification and the product drawing, the product drawing shall take precedence. In the event of conflict between the requirements of this specification and the referenced documents, this specification shall take precedence.

A. EIA-364 :

The Test Sequence and Test Procedures for Electrical Connectors and Sockets.

## 3. Material of Components :

	Component	Material	Finish
1	Housing	Thermoplastic ( UL94V-0) (PA6T无卤)	None
2	Contact	Copper Alloy (黄铜)	Refer to Ordering Information

## 4. Design and Construction :

Product shall be of the design, construction and physical dimensions specified in the applicable product drawing.



**Product Specification**

**1.27mm PITCH 2X44P 1272WVS CONNECTOR SERIES**

**5. Performance and Test Descriptions :**

The product is designed to meet the electrical, mechanical and environmental performance requirements specified below. All tests are performed at ambient temperature unless otherwise specified.

**5.1 Electrical Performance :**

	Test Items	Test Procedures & Condition	Requirements
1	Contact Resistance	EIA 364-23  Subject mated contacts assembled in housing to closed circuit current of 100 mA maximum at open circuit at 50 mV maximum.	1. Initial value : 20 mΩ max. 2. Final value : 30 mΩ max.
2	Insulation Resistance	EIA 364-21  Measure by applying test potential between the adjacent contacts, and between the contacts and ground in the mated connector assemblies.  Test Voltage : 1000 V DC.	Not less than 1000 MΩ
3	Dielectric Withstanding Voltage	EIA 364-20  Measure by applying test potential between the adjacent contacts, and between the contacts and ground in the mated connector assemblies.  Test Potential : 500Vac at sea level Test Duration : 60 seconds	1.No disruptive discharge, leakage or deterioration. 2. Current leakage : <0.5 mA



**Product Specification**

**1.27mm PITCH 2X44P 1272WVS CONNECTOR SERIES**

**5.2 Mechanical Performance :**

	Test Items	Test Procedures & Condition	Requirements
1	Contact Retention	EIA 364-29  Subject unmated connector shall be mounted in a position of axial alignment of the contacts with the plunger of the test gauge to measure the withstand ability of the contact retaining system.	Minimum 200 gf ( Per PIN )
2	Durability	EIA 364-09  Mate and Unmate connector assemblies at maximum rate of 200 cycles per hour.  Test Cycles : 300 cycles Min	1. No evidence of damage.  2. The electrical performances meet the spec. specified in paragraph 5.1
3	Solderability	EIA 364-52 Category 3  Subject unmated connectors should be tested according to the condition listed below :  Steam Aging Temperature : 90 ~ 96°C  Steam Aging Duration: 8 hours±5 min.  Soldering Temperature : 245±5°C  Soldering Time : 4 ~ 5 seconds	Continuous solder coating with a minimum 95% coverage.



**Product Specification**

**1.27mm PITCH 2X44P 1272WVS CONNECTOR SERIES**

	Test Items	Test Procedures & Condition	Requirements
4	Vibration	<p>EIA 364-28 Condition V Test letter A</p> <p>Subject mated connectors should be tested according to the condition listed below :</p> <p>Test condition : Random Frequency : 50 ~ 2000 Hz PSD value : 3.13 Grms minimum Duration : 15 minutes/axis Times: Each of three mutually perpendicular planes.</p>	<ol style="list-style-type: none"><li>1. No evidence of damage.</li><li>2. No discontinuities of 1<math>\mu</math>s or longer duration.</li><li>3. The electrical performances meet the spec. specified in paragraph 5.1</li></ol>
5	Physical Shock	<p>EIA 364-27 Condition H</p> <p>Subject mated connectors should be tested according to the condition listed below :</p> <p>Wave form : Half-sine Peak acceleration : 30 G's Duration : 11 ms Times: 3 shocks in each direction applied along three mutually perpendicular planes, total 18 shocks.</p>	<ol style="list-style-type: none"><li>1. No evidence of damage.</li><li>2. No discontinuities of 1<math>\mu</math>s or longer duration.</li><li>3. The electrical performances meet the spec. specified in paragraph 5.1</li></ol>



**Product Specification**

**1.27mm PITCH 2X44P 1272WVS CONNECTOR SERIES**

**5.3 Environmental Performance :**

	Test Items	Test Procedures & Condition	Requirements
1	Humidity ( Temperature Cycling )	EIA 364-31 Method III Test Condition A  Subject mated connectors should be tested according to the condition listed below :  Temperature : 25 ~ 65°C Humidity : 90 ~ 95% ( R.H ) Duration : 96 hours	1. No evidence of damage.  2. The electrical performances meet the spec. specified in paragraph 5.1
2	Thermal Shock	EIA 364-32 Test Condition I  Subject mated connectors should be tested according to the condition listed below : Temperature : -55 ~ 85°C Cycles : 5 Exposure time at temperature extremes : 30 minutes	1. No evidence of damage.  2. The electrical performances meet the spec. specified in paragraph 5.1
3	Salt Spray	EIA 364-26 Test Condition A  Subject mated and unmated connectors should be tested according to the condition listed below :  Temperature : 35±1.1°C Humidity : 95 ~ 98% ( R.H ) PH Value : 6.5 ~ 7.2 Duration 24hours	1. No evidence of damage.  2. The electrical performances meet the spec. specified in paragraph 5.1



**Product Specification**

**1.27mm PITCH 2X44P 1272WVS CONNECTOR SERIES**

	Test Items	Test Procedures & Condition	Requirements
4	Temperature Life	EIA 364-17 Test Condition 3 Method A  Subject mated connectors should be tested according to the condition listed below :  Temperature : 85±2°C  Duration : 96 hours	1. No evidence of damage.  2. The electrical performances meet the spec. specified in paragraph 5.1
5	Resistance to Soldering Heat	EIA 364-56 Procedure 3 Test Condition C  1. PA6T Thermoplastic Canbe withstand 260±5°C Temperature IR Stove. Time: 5~10 seconds  Under PCB board Temperature: 260±5°C Time: 5~10 seconds	1. No evidence of damage.  2. The electrical performances meet the spec. specified in paragraph 5.1  3. The mechanical performances meet the spec. specified in paragraph 5.2