



- 规格:
1. 额定电压: 30V AC / DC
 2. 额定电流: 0.2A AC / DC
 3. 接触电阻: ≤30mΩ
 4. 环境测试后 (接触电阻): ≤40mΩ
 5. 绝缘电阻: ≥100MΩ
 6. 耐压值: 200V AC/minute
 7. 工作温度: -25°C~+85°C

0600 HI- XX G- LP XX
 ① ②③ ④ ⑤ ⑥ ⑦

- ① 系列
- ② 类别: H-HSG
- ③ 外观形态: I-HSG加五金件组立品
- ④ PIN数或防呆KEY形态: 单排-XX
- ⑤ 特殊码: 空码-镀锡 G-镀金 G3-镀金3U"
- ⑥ 材质: LP-LCP 94V-0 NO-PA66 94V-0
- ⑦ 颜色: 空码-本色或普通色
HF-无卤

0600HI-XXG3-LPHF	LCP UL 94V-0 Halogen Free	AWG#36	0.29mm(Max)	Phosphor Bronze	Gold-Flash	0600W	1,000Pcs
0600HI-XX-N0HF	PA66 UL 94V-0 Halogen Free				Tin-Plated		
0600HI-XXG-N0HF	PA66 UL 94V-0 Halogen Free				Gold-Flash		
0600HI-XX-LP	LCP UL 94V-0				Tin-Plated		
0600HI-XXG-LP					Gold-Flash		
PART NO	Material	Wire Range	Insulation O.D.	Material (Terminal)	Finish (Terminal)	Mates With CSWB Wafer	Q' ty/Bag

Poles	Dimensions(mm)		Poles	Dimensions(mm)	
	A	B		A	B
02	1.80	0.60	13	8.40	7.20
03	2.40	1.20	14	9.00	7.80
04	3.00	1.80	15	9.60	8.40
05	3.60	2.40	16	10.20	9.00
06	4.20	3.00	17	10.80	9.60
07	4.80	3.60	18	11.40	10.20
08	5.40	4.20	19	12.00	10.80
09	6.00	4.80	20	12.60	11.40
10	6.60	5.40	21	13.20	12.00
11	7.20	6.00	22	13.80	12.60
12	7.80	6.60			

				GENERAL TOLERANCE X ±0.20 .XX ±0.15 .XXX ±0.08				昆旺精密连接器有限公司 VIGORCONN PRECISION CONNECTOR CO., LTD				PART NO. 0600HI-XXG-LP			
				PROJECT 								TITLE. 0.60mm Crimp Style connectors			
DATE	OLD REV	NEW REV	ECN	DESCRIPTION	CHECK	APPROVAL	Kim Huang	Jova Lau	Xiao Wen Xuan	2019/05/15	UNIT MM	SCALE 1:1	NUMBER A-00	REV A	